



# Mech-Eye NANO-GL

## Palm-Sized Industrial 3D Camera

High Precision · Small Size · Fast Acquisition  
High Flexibility · Easy Integration · Competitive Price



MTBF (Mean Time Between Failures)  $\geq$  40,000 hours

### Specifications

Working distance: 300–600 mm

Near FOV: 220 × 150 mm @ 0.3 m

Far FOV: 440 × 300 mm @ 0.6 m

Resolution: 1280 × 1024

Megapixels: 1.3 MP

Operating temperature: 0–45°C

Communication interface: Gigabit Ethernet

IP rating: IP65

Image sensor: Sony CMOS for high-end machine vision

Point Z-value repeatability ( $\sigma$ )<sup>[1]</sup>: 0.1 mm @ 0.5 m

Measurement accuracy (VDI/VDE)<sup>[2]</sup>: 0.1 mm @ 0.5 m

Typical capture time: 0.6–1.1 s

Baseline: 68 mm

Dimensions: 145 × 51 × 85 mm

Weight: 0.7 kg

Input: 24 V DC, 1.5 A


Light source: Blue LED (459 nm, RG2)/ White LED (RG2)

Safety and EMC: CE/FCC/VCCI/KC/ISED/NRTL


Cooling: Passive

MTBF (Mean Time Between Failures) :  $\geq$  40,000 hours


### Field of View (mm)



### Point Clouds



Precision component



0.68 mm thick workpiece



Car charging port



Small parts

Specifications are subject to the official website.

[1] One standard deviation of 100 Z-value measurements of the same point. The measurement target was a ceramic plate.

[2] According to VDI/VDE 2634 Part II.

